To: USPTO Central Fax Page 4 of 7

APPLICANT(S): Marcelo Krygier

SERIAL NO.:

10/766,320

FILED: Page 2

01/29/2004

AMENDMENTS TO THE CLAIMS

.

Please add or amend the claims to read as follows, and cancel without prejudice or disclaimer to resubmission in a divisional or continuation application claims indicated as cancelled:

- ١. (Currently Amended) A method for operating a non-volatile memory device comprising: using one or more unused bits of an address argument of a command as an addressing mode field to determine whether said address argument is a byte address argument or a block address argument.
- 2. (original) The method of claim 1 comprising: determining that the address argument is the byte address argument when the addressing mode field is zero.
- . 3. (original) The method of claim 1 comprising: determining that the address argument is the block address argument when the addressing mode field is one.
 - 4. (original) The method of claim 2 further comprising: accessing a byte address within a memory unit according to the byte address argument if said address argument is a byte address argument.
 - (original) The method of claim 3 further comprising: accessing a block 5. address within a memory unit according to the block address argument if said address argument is a block address argument.
 - (original) The method of claim 1, wherein using said one or more unused 6. bits comprises using a least significant bit of said address argument.
 - (original) The method of claim 1, wherein using said one or more unused 7. bits comprises using a most significant bit of said address argument.
 - (original) An apparatus comprising: a non-volatile memory unit; and a 8. controller to determine whether an addressing mode to access said memory unit is a byte addressing mode or a block addressing mode and to send a

To: USPTO Central Fax Page 5 of 7

SERIAL NO.: FILED:

10/766,320 01/29/2004

Page 3

command to access data within said memory unit according to said addressing mode.

- 9. (original) The apparatus of claim 8, wherein said memory unit is a multi media card (MMC).
- 10. (original) The apparatus of claim 8, wherein said memory unit is a secure digital (SD) memory card.
- (original) The apparatus of claim 8, wherein the addressing mode is 11. associated with the ninth bit of a 48-bit command having a 32-bit address argument.
- 12. (original) The apparatus of claim 8, wherein the addressing mode is associated with the 31-st bit of a 48-bit command having a 32-bit address argument.
- 13. (currently amended) [An article comprising] a storage medium having stored thereon instructions that, when executed by a computing platform functionally associated with a non-volatile memory device, result in: using an addressing mode field of an address argument of a command to determine whether said address argument is a byte address argument or a block address argument.
- (original) The storage medium [article] of claim 13 wherein the 14. instructions, when executed result in: using one or more unused bits of the address argument as the addressing mode field.
- (original) The storage medium [article] of claim 13, wherein the 15. instructions when executed further result in: determining that the address argument is the byte address argument when the addressing mode field is zero.
- (original) The storage medium [article] of claim 13, wherein the 16. instructions when executed further result in: determining that the address argument is the block address argument when the addressing mode field is one.